


C-82626 GLUTE & HAMSTRING MACHINE



Page: 1 of 4



C-82626 GLUTE & HAMSTRING MACHINE PACKING LIST



C-82626 GLUTE AND HAMSTRING MACHINE ASSEMBLY INSTRUCTIONS

THIS UNIT REQUIRES (1) 9/16 WRENCH AND (1) 11/16 WRENCH FOR ASSEMBLY. DO NOT TIGHTEN HARDWARE UNTIL INSTRUCTED TO.

- (1) PUSH (4) 2 X 4 FOOT ONTO BASE. ATTACH POST TO BASE WITH (2) 3/8 X 3 BOLTS, (1) 3/8 X 5 BOLT, (6) 3/8 FLAT WASHERS AND (3) 3/8 LOCKNUTS.
- (2) PUSH (2) REDUCER BUSHINGS INTO SLIDE. PLACE SLIDE OVER BODY. ATTACH BODY TO BASE WITH (2) 3/8 X 3 BOLTS, (4) 3/8 FLAT WASHERS AND (2) 3/8 LOCKNUTS. ATTACH BODY TO POST WITH (3) 3/8 X 1 BOLTS AND (3) 3/8 FLAT WASHERS. PLACE UNIT ON LEVEL SURFACE AND TIGHTEN HARDWARE. INSTALL (1) PIN LOCK AND (2) HAND KNOBS.
- (3) ATTACH PADS TO PAD MOUNT WITH (4) 3/8 X 2 1/2 BOLTS AND (4) 3/8 FLAT WASHERS. CENTER PAD ON PAD MOUNT AND TIGHTEN HARDWARE. DO NOT OVER TIGHTEN. ATTACH PAD MOUNT TO POST WITH (2) 3/8 X 2 1/2 BOLTS, (4) 3/8 FLAT WASHERS AND (2) 3/8 LOCKNUTS. TIGHTEN HARDWARE.
- (4) PUSH (2) REDUCER BUSHINGS INTO FOOT CATCH. NOTE FOOT PLATE & FOOT CATCH ARE WELDED TOGETHER. PLACE FOOT CATCH OVER SLIDE. SET HEIGHT WITH (1) CR. PIN LOCK AND (1) HAND KNOB. PUSH (4) 4 X 16 CUSHIONS ONTO FOOT CATCH. INSTALL (4) CUSHION CAPS WITH (4) 3/8" X 1" BOLTS & (4) 3/8" LARGE WASHERS. INSTALL (6) 2 PLUGS AND (2) 1 X 2 PLUGS. LUBE SLIDE AND BODY WITH LEMON PLEDGE FURNITURE POLISH. GRIPS, REDUCERS, FEET AND PLUGS MAY BE INSTALLED AT FACTORY.

HARDWARE LIST

- (4) 3/8 X 1 BOLT
- (8) 3/8 X 2 ½ BOLT
- (4) 3/8 X 3 BOLT
- (1) 3/8 X 5 BOLT
- (29) 3/8 FLAT WASHER
- (11) 3/8 LOCKNUT
- (2) PIN LOCK
- (4) HAND KNOB
- (6) 2 PLUG
- (2) 2 X 4 PLUG
- (4) 2 X 4 FOOT
- (4) REDUCER BUSHING
- (4) HAND GRIP
- (4) 3/8" LARGE WASHERS

NOTE: ALL SIZES ARE IN INCHES